



2. 1/2"-8NPSM internal thread	
Middle Dia	2.762-2.768"
Min Dia	2.705-2.715"
Max Dia	2.843-2.849"

Remark
 1. Product type identification see outer packaging logo.
 2. The product color is consistent with the color of the tape packaging box.

Technical Parameters

Model	Opening Size	(Ltrs.)	Size Parameters (mm)								Base	Weight (kg)
			D1	H1	H2	F	WA	WLB	WB	WLA		
10×13	T 2.5"	13.0	258	331	178	10	5	2	5	1	NO	1.2±0.2
10×17	T 2.5"	16.4	258	425	245	50	5	2	5	1	NO	2.3±0.2
10×19	T 2.5"	18.8	258	489	297	100	5	2	5	1	NO	2.7±0.2
10×24	T 2.5"	25.0	258	617	425	100	5	2	5	1	NO	3.1±0.3
10×28	T 2.5"	30.0	258	717	515	100	5	2	5	1	NO	3.5±0.4
10×35	T 2.5"	38.8	258	891	705	100	5	2	5	1	NO	3.9±0.4
10×44	T 2.5"	50.0	258	1130	935	100	5	2	5	1	NO	4.8±0.4
10×54	T 2.5"	62.5	258	1375	1195	100	5	2	5	1	NO	5.7±0.4

Note:
 1. The vacuum valve must be installed on the device.
 2. Operation Instructions
 A. Max working pressure: 10.5bar (150Psi)
 B. Temperature Range: 1-50°C (34-127°F)
 C. Maximum vacuum: 17Kpa (5" Hg)

Sign			Hebei Chengda WaterTechnology Co., Ltd.			
Designer	Signature Chengyang Sun	Date 2024. 7. 16	Material:	FRP	Projection:	
Review	Jingwei Hu	2024. 7. 18	Model:	10", 2.5"T	Name:	FRP tank
Approve			Version number:	00	Description of Change Version	Drawing No.: CD-22-09-28/21
Please don't measure the size of the drawing.			Unit:	mm	1 Page Page 1	