



	2. 1/2"-8NPSM	internal thread
Middle Dia	2.762-2.768"	
Min Dia	2.705-2.715"	
Max Dia	2.843-2.849"	

Technical Parameters

Model	Opening Size	VOL (Ltrs.)	Size Parameters (mm)											Base Standand	Weight (kg)
			D1	D	H±6	H1	H2	L	F	WA	WLA	WB	WLB		
610	±2.5"	3.2	156	166	259	254	161	95	10	5	2	4	1	Standand	0.9±0.1
613	±2.5"	4.7	156	166	346	341	247	95	10	5	2	4	1	Standand	1.2±0.1
617	±2.5"	6.5	156	166	437	432	339	95	50	5	2	4	1	Standand	1.5±0.2
618	±2.5"	7.0	156	166	464	459	364	95	50	5	2	4	1	Standand	1.5±0.2
629	±2.5"	12.0	156	166	741	736	643	95	100	5	2	4	1	Standand	2. ±0.2
635	±2.5"	14.8	156	166	894	889	796	95	100	5	2	4	1	Standand	2.2±0.3

Note :

- The vacuum valve must be installed on the device
- Operation Instructions
 - Max working pressure 8bar(125Psi)
 - Temperature Range: 1-50°C (34-127°F)
 - Maximum vacuum: 17Kpa (5" Hg)

Remark

- Product type identification see outer packaging logo.
- The product color is consistent with the color of the tape packaging box.

Sign			Hebei Chengda WaterTechnology Co., Ltd.			
	Signa	Date	Material FRP	FRP	Projection :	
Design er	Chengyang Sun	2024.07.18	Model	6" in diameter, 2 5" top port	Name: FRP tank	
Review	Jingwei Hu	2024.07.18	Version number:	00	Description of Change Version	Drawing No. CD-22-09-27/01
Appro ve			Please don't measure the size of the drawing		Unit: mm	1 Page Page 1