



2. 1/2"-8NPSM Internal thread	
Medium Dia	2.762-2.768"
Small Dia	2.705-2.715"
Large Dia	2.843-2.849"

Remark  
 1. Product type identification see outer packaging logo.  
 2. The product color is consistent with the color of the tape packaging box.

Technical Parameters

Model	Opening Size	VOL (Ltrs.)	Size Parameters (mm)								Base	Weight (kg)
			D1	H1	H2	F	WA	WLB	WB	WLA		
10×13	2.5"T	13.0	258	331	166	10	4.8	1.8	5	1	none	1.1±0.2
10×17	2.5"T	16.4	258	425	245	50	4.8	1.8	5	1	none	2.2±0.2
10×19	2.5"T	18.8	258	489	297	100	4.8	1.8	5	1	none	2.5±0.2
10×24	2.5"T	25.0	258	617	425	100	4.8	1.8	5	1	none	3±0.3
10×28	2.5"T	30.0	258	717	515	100	4.8	1.8	5	1	none	3.5±0.4
10×35	2.5"T	38.8	258	891	705	100	4.8	1.8	5	1	none	3.9±0.4
10×44	2.5"T	50.0	258	1130	935	100	4.8	1.8	5	1	none	4.5±0.4
10×54	2.5"T	62.5	258	1375	1195	100	4.8	1.8	5	1	none	5.5±0.4

Note:  
 1. The vacuum valve must be installed on the device.  
 2. Operation Instructions:  
 A. Max working pressure: 8Bar (125Psi)  
 B. Temperature Range: 1-50°C (34-127°F)  
 C. Maximum vacuum: 17Kpa (5"Hg)

Sign			Hebei Chengda WaterTechnology Co.,Ltd.			
	Signature	Date	Material:	FRP	Projection:	$\begin{matrix} \text{---} \\ \oplus \end{matrix}$
Designer	Chengyang Sun	2024.07.18	Model:	10", 2.5"T	Name:	FRP tank
Review	Jingwei Hu	2024.07.18	Version number:	00	Description of Change Version	Drawing No. CD-21-12-30/10
Approve			Please don't measure the size of the drawing		Unit: mm	1 Page Page 1