



	2. 1/2"-8NPSM	Internal thread
Middle Dia	2.762-2.768"	
Min Dia	2.705-2.715"	
Max Dia	2.843-2.849"	

Remark  
 1. Product type identification see outer packaging logo.  
 2. The product color is consistent with the color of the tape packaging box.

Technical Parameters

Model	Opening Size	VOL (Ltrs.)	Size Parameters (mm)											Base	Weight (kg)
			D1	D	H±6	H1	H2	L	F	WA	WLA	WB	WLB		
12×36	2.5"T	55.6	306	318	920	895	1000	180	100	5.5	2	5.5	1.5	Standand	5±0.5
12×48	2.5"T	77.5	306	318	1233	1205	1000	180	100	5.5	2	5.5	1.5	Standand	6±0.5
12×52	2.5"T	85.3	306	318	1333	1325	1100	180	100	5.5	2	5.5	1.5	Standand	7.5±0.5
12×65	2.5"T	108.5	306	318	1663	1656	1430	180	100	5.5	2	5.5	1.5	Standand	9±0.5

Note:  
 1. The vacuum valve must be installed on the device.  
 2. Operation Instructions:  
 A. Max working pressure: 8Bar (125Psi)  
 B. Temperature Range: 1-50°C (34-127°F)  
 C. Maximum vacuum: 17Kpa (5"Hg)

Sign			Hebei Chengda WaterTechnology Co., Ltd.			
	Signature	Date	Material:	FRP	Projection:	
Designer	Chengyang Sun	2024. 07. 18	Model:	12", 2.5"T	Name:	FRP tank
Review	Jingwei Hu	2024. 07. 18	Version number:	00	Description of Change Version	Drawing No. CD-22-09-27/12
Approve			Please don't measure the size of the drawing		Unit: mm	1 Page Page 1