



- 1、设计压力3.1MPa (450PSI)  
Design Pressure 3.1MPa(450PSI)
- 2、设计温度66℃ (150° F)  
Design Temperature 66℃ (150° F)
- 3、最低允许温度-10℃ (14° F)  
Min Temperature -10℃ (14° F)
- 4、工作介质为PH3-10的水  
Media:Water PH3-10
- 5、项目10仅在原水端; 项目5仅在浓水端;  
Item 10 is at the RAW end only; item 5 is at the concentrated end only;
- 6、请按照说明书正确使用  
Please operate it according to operation manual

| 长度编码<br>Length | S<br>(mm) | L<br>(mm) | P<br>(mm) | 重量<br>WEIGHT<br>(kg) |
|----------------|-----------|-----------|-----------|----------------------|
| 1              | 715       | 1435      | 1120      | 35.5                 |
| 2              | 1731      | 2453      | 2136      | 41.5                 |
| 3              | 2747      | 3469      | 3152      | 47.5                 |
| 4              | 3763      | 4485      | 4168      | 53.5                 |
| 5              | 4779      | 5501      | 5184      | 59.5                 |
| 6              | 5795      | 6517      | 6200      | 65.5                 |
| 7              | 6811      | 7533      | 7216      | 71.5                 |

| 名称  | 数量  | 材料                      |
|---|-----|-------------------------|
| 18 垫片 shim block                          | 3   | 工程塑料Engineering Plastic |
| 17 卡箍 PERMEATE RETAINING RING             | 2   | SUS304                  |
| 15/16 钢带STRAP+螺丝SCREWHEAD (螺栓尺寸: M8*90)   | 2-3 | A-666, 304+A216         |
| 14 鞍座SADDLE (3芯以上均为3个)                    | 2-3 | TPU (S60D)              |
| 13 挡块螺丝 BAFFLE FIXING BOLTS               | 6   | SUS304                  |
| 12 挡块 LINK STOPPER                        | 6   | 铝合金                     |
| 11 承压头 (450Psi) HEAD SEAL                 | 2   | ABS                     |
| 10 适配器ADAPTOR                             | 2   | ABS                     |
| 08/09 适配器大/小O型圈ADAPTOR LARGE/SMALL O GLUB | 4+4 | EPDM512+硅胶              |
| 07 π型密封胶圈 π SEALING RUBBER RING           | 2   | 硅胶                      |
| 06 承载板BBARING PLATE                       | 2   | 铸铝                      |
| 05 止推环THRUST CONE                         | 1   | 工程塑料Engineering Plastic |
| 04 侧口两圈 SIDE DORT                         | 2   | SUS304                  |
| 03 侧口SIDE PORT                            | 2   | SUS304                  |
| 02 侧口密封胶圈SIDE PORT SEAL RING              | 4   | EPDM 512                |
| 01 壳体SHELL                                | 1   | FIBER GLASS +EPOXY      |

| 原浓水口规格      | D   | H   |
|-------------|-----|-----|
| 1.5" (DN40) | 246 | 152 |
| 2" (DN50)   | 248 | 152 |

|    | NAME | DATE       |
|----|------|------------|
| 设计 | 卢景伟  | 2022.12.27 |
| 审核 |      |            |
| 审批 |      |            |

THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY

**河北水处理科技有限公司**  
Hebei Chengda water Technology Co., Ltd

型号 TYPE: **G80S450**      单位UNIT: **MM**

仅供参考, 零部件以图纸为准, 变更不另行通知