



- 1、设计压力3.1MPa (450PSI)
Design Pressure 3.1MPa (450PSI)
- 2、设计温度66℃ (150° F)
Design Temperature 66℃ (150° F)
- 3、最低允许温度-10℃ (14° F)
Min Temperature -10℃ (14° F)
- 4、工作介质为PH3-10的水
Media: Water PH3-10
- 5、项目10仅在原水端；项目5仅在浓水端；
项目3为常规1.5寸。
Item 10 is at the RAW end only; item 5 is at the concentrated end only; item 3 is at the conventional 1.5 inch.
- 6、请按照说明书正确使用
Please operate it according to operation manual

长度编码 Length	S (mm)	L (mm)	P (mm)	重量 WEIGHT (kg)	名称	数量	材料
1	715	1435	1120	36	18 垫片 shim block	3	工程塑料Engineering Plastic
2	1731	2453	2136	45	17 卡箍 PERMEATE RETAINING RING	2	SUS304
3	2747	3469	3152	54	15/16 钢带STRAP+螺丝SCREWHEAD (螺栓尺寸: M8*90)	2-3	A-666, 304+A216
4	3763	4485	4168	63	14 鞍座SADDLE (3芯以上均为3个)	2-3	TPU (S60D)
5	4779	5501	5184	72	13 挡块螺丝 BAFFLE FIXING BOLTS	6	SUS304
6	5795	6517	6200	81	12 挡块 LINK STOPPER	6	铝合金
7	6811	7533	7216	90	11 承压头 (450Psi) HEAD SEAL	2	ABS
					10 适配器ADAPTOR	2	ABS
					08/09 适配器大/小O型圈ADAPTOR LARGE/SMALL O GLUB	4+4	EPDM512+硅胶
					07 π型密封胶圈 π SEALING RUBBER RING	2	硅胶
					06 承载板BBARING PLATE	2	铸铝
					05 止推环THRUST CONE	1	工程塑料Engineering Plastic
					04 侧口两圈 SIDE DORT	2	SUS304
					03 侧口SIDE PORT	2	304不锈钢
					02 侧口密封胶圈SIDE PORT SEAL RING	4	EPDM 512
					01 壳体SHELL	1	FIBER GLASS +EPOXY

	NAME	DATE	Winder-G 河北成达水处理科技有限公司 Hebei Chengda Water Technology Co., Ltd	
设计	卢景伟	2022.12.27	型号 TYPE	单位UNIT:
审核			G80S450	MM
审批			仅供参考，零部件以图纸为准，变更不另行通知	
THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY				