



- 设计压力 3.1MPa (450PSI)
Design Pressure 3.1MPa (450PSI)
- 设计温度 66°C (150° F)
Design Temperature 66°C (150° F)
- 最低允许温度 -10°C (14° F)
Min Temperature -10°C (14° F)
- 工作介质为 PH3-10 的水
Media: Water PH3-10
- 净水口压力为 0.88MPa (12.5PSI)
0.88MPa (12.5PSI)
- 项目 3 数量由客户选择决定; 项目 5 仅在浓水端
The number of items 3 is determined by the customer's choice; Item 5. At the end of concentrated water only
- 图纸仅供参考, 具体以实物为准
Drawings are for reference only, in kind
- 请按照说明书正确使用
Please operate it according to operation manual

长度编码 Length	S (mm)	L (mm)	P (mm)	重量 WEIGHT (kg)
1	693 (27.3)	1453 (57.2)	1147 (45.2)	37 (81.4)
2	1709 (67.3)	2469 (97.2)	2163 (85.2)	48.5 (106.7)
3	2725 (107.3)	3485 (137.2)	3179 (125.2)	60 (132)
4	3741 (147.3)	4501 (177.2)	4195 (165.2)	71.5 (157.3)
5	4757 (187.3)	5517 (217.2)	5211 (205.2)	83 (182.6)
6	5773 (227.3)	6533 (257.2)	6227 (245.2)	94.5 (207.9)
7	6789 (267.3)	7549 (297.2)	7243 (285.2)	106 (233.2)

18	垫片 shim block	3	工程塑料 Engineering Plastic
17	紧固螺母 FASTENING NUT	2	工程塑料 Engineering Plastic
15/16	挡块+挡块螺丝 LINK STOPPER+BAFFLE FIXING BOLTS	6	SUS304
13/14	钢带 STRAP+螺丝 SCREWHEAD (螺栓尺寸: M8*90)	2-3	A-666, 304+A216
12	鞍座 SADDLE (3芯以上均为3个)	2-3	TPU (S60D)
11	密封板 SEALBOARD	2	ABS
10	适配器 ADAPTOR	2	ABS
09	适配器小 O 型圈 ADAPTOR SMALL O GLUE	4	硅胶
08	适配器大 O 型圈 ADAPTOR LARGE O GLUE	4	EPDM 512
07	密封板 O 型圈 SEALING PLATE O-RING	2	EPDM 512
06	承载板 BEARING PLATE	2	SB-209, 6061-T651
05	止推环 THRUST CONE	1	工程塑料 Engineering Plastic
04	侧口两圈 SIDE DORT	2-4	SUS304
03	侧口 SIDE PORT (1.5" 2" 2.5" 客户选择)	2-4	316L 不锈钢 AISI316
02	侧口密封圈 SIDE PORT SEAL RING	4	EPDM 512
01	壳体 SHELL	1	FIBER GLASS +EPOXY

原浓水口规格	D	H
1.5" (DN40)	246	150
2" (DN50)	248	151
2.5" (DN65)	258	156

SIGNATURE		
	NAME	DATE
设计	卢景伟	2022.12.27
审核		
审批		

Winder 河北成达水处理科技有限公司
Hebei Chengda Water Technology Co., Ltd

型号 TYPE W80S450	单位 UNIT: MM
---------------------------	-----------------------

仅供参考, 零部件以图纸为准, 变更不另行通知

THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY