



- 1、设计压力2.1MPa (300PSI)
Design Pressure 2.1MPa(300PSI)
- 2、设计温度66℃ (150° F)
Design Temperature 66℃ (150° F)
- 3、最低允许温度-10℃ (14° F)
Min Temperature -10℃ (14° F)
- 4、工作介质为PH3-10的水
Media:Water PH3-10
- 5、项目10仅在原水端; 项目5仅在浓水端;
Item 10 is at the RAW end only; item 5 is at the concentrated end only;
- 6、请按照说明书正确使用
Please operate it according to operation manual

长度编码 Length	S (mm)	L (mm)	P (mm)	重量 WEIGHT (kg)	名称	数量	材料
1	715	1435	1120	31	18 垫片 shim block	3	工程塑料Engineering Plastic
2	1731	2453	2136	37.5	17 卡箍 PERMEATE RETAINING RING	2	SUS304
3	2747	3469	3152	43.5	15/16 钢带STRAP+螺丝SCREWHEAD (螺栓尺寸: M8*90)	2-3	A-666, 304+A216
4	3763	4485	4168	49.5	14 鞍座SADDLE (3芯以上均为3个)	2-3	TPU (S60D)
5	4779	5501	5184	55.5	13 挡块螺丝 BAFFLE FIXING BOLTS	6	SUS304
6	5795	6517	6200	61.5	12 挡块 LINK STOPPER	6	铝合金
7	6811	7533	7216	67.5	11 承压头 (450Psi) HEAD SEAL	2	ABS
					10 适配器ADAPTOR	2	ABS
					08/09 适配器大/小O型圈ADAPTOR LARGE/SMALL O GLUB	4+4	EPDM512+硅胶
					07 π型密封胶圈 π SEALING RUBBER RING	2	硅胶
					06 承载板BBARING PLATE	2	铸铝
					05 止推环THRUST CONE	1	工程塑料Engineering Plastic
					04 侧口两圈 SIDE DORT	2	SUS304
					03 侧口SIDE PORT	2	SUS304
					02 侧口密封胶圈SIDE PORT SEAL RING	4	EPDM 512
					01 壳体SHELL	1	FIBER GLASS +EPOXY

原浓水口规格	D	H
1.5" (DN40)	244	148
2" (DN50)	246	150

	NAME	DATE
设计	卢景伟	2022.12.27
审核		
审批		

THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY

河北水处理科技有限公司
Hebei Chengda water Technology Co., Ltd

型号 TYPE	单位UNIT:
G80S300	MM

仅供参考, 零部件以图纸为准, 变更不另行通知