



- 设计压力2.1MPa (300PSI)
Design Pressure 2.1MPa (300PSI)
- 设计温度66℃ (150° F)
Design Temperature 66℃ (150° F)
- 最低允许温度-10℃ (14° F)
Min Temperature -10℃ (14° F)
- 工作介质为PH3-10的水
Media: Water PH3-10
- 项目10仅在原水端; 项目5仅在浓水端;
项目3为常规1.5寸。
Item 10 is at the RAW end only; item 5 is at the concentrated end only; item 3 is at the conventional 1.5 inch.
- 请按照说明书正确使用
Please operate it according to operation manual

18	垫片 shim block	3	工程塑料Engineering Plastic
17	PERMEATE RETAINING RING	2	SUS304
15/16	钢带STRAP+螺丝SCREWHEAD (螺栓尺寸: M8*90)	2-3	A-666, 304+A216
14	鞍座SADDLE (3芯以上均为3个)	2-3	TPU (S60D)
13	挡块螺丝 BAFFLE FIXING BOLTS	6	SUS304
12	挡块 LINK STOPPER	6	铝合金
11	承压头 (300Psi) HEAD SEAL	2	ABS
10	适配器ADAPTOR	2	ABS
08/09	适配器大/小型ADAPTOR LARGE/SMALL O GLUE	4+4	BPDM512+硅胶
07	π型密封胶圈 π SEALING RUBBER RING	2	硅胶
06	承载板 BEARING PLATE	2	铸铝
05	止推环 THRUST CONE	1	工程塑料Engineering Plastic
04	侧口两圈 SIDE DORT	2-4	SUS304
03	侧口 SIDE PORT	2-4	304不锈钢
02	侧口密封圈 SIDE PORT SEAL RING	4	BPDM 512
01	壳体 SHBL	1	FIBER GLASS +EPOXY
	名称	数量	材料

长度编码 Length	S (mm)	L (mm)	P (mm)	重量 (kg)
1	715	1493	1146	42
2	1731	2511	2162	49
3	2747	3527	3178	56
4	3763	4543	4194	63
5	4779	5559	5210	70
6	5795	6575	6226	77
7	6811	7591	7242	84

原浓水口规格	D	H
2.5" (DN65)	252	153
3" (DN80)	260	159

	NAME	DATE
设计	卢景伟	2022.12.27
审核		
审批		

THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY

Winder — G 河北成达水处理科技有限公司
Hebei Chengda Water Technology Co., Ltd

型号 TYPE	单位 UNIT:
G80S300-DN65/DN80	MM

仅供参考, 零部件以图纸为准, 变更不另行通知