



- 1、设计压力 6.9MPa (1000PSI)
Design Pressure 6.9MPa (1000PSI)
- 2、设计温度 66°C (150° F)
Design Temperature 66°C (150° F)
- 3、最低允许温度 -10°C (14° F)
Min Temperature -10°C (14° F)
- 4、工作介质为 PH3-10 的水
Media: Water PH3-10
- 5、净水口压力为 0.88MPa (12.5PSI)
0.88MPa (12.5PSI)
- 6、项目 3 数量由客户选择决定; 项目 5 仅在浓水端
The number of items 3 is determined by the customer's choice; Item 5. At the end of concentrated water only
- 7、图纸仅供参考, 具体以实物为准
Drawings are for reference only, in kind
- 8、请按照说明书正确使用
Please operate it according to operation manual

长度编码 Length	S (mm)	L (mm)	P (mm)	重量 WEIGHT (kg)	名称	数量	材料
1	632 (24.9)	1532 (60.3)	1127 (44.4)	68 (149.6)	19 垫片 shim block	3	工程塑料 Engineering Plastic
2	1648 (64.9)	2548 (100.3)	2143 (84.4)	87 (191.4)	18 紧固螺母 FASTENING NUT	2	工程塑料 Engineering Plastic
3	2664 (104.9)	3564 (140.3)	3159 (124.4)	106 (233.2)	17 螺栓 BOLT	6	SUS304
4	3680 (144.9)	4580 (180.3)	4175 (164.4)	125 (275)	16 定位环 POSITIONING RING	2	工程塑料 Engineering Plastic
5	4696 (184.9)	5596 (220.3)	5191 (204.4)	144 (316.8)	15 挡块 BLOCK	6	SUS316L
6	5712 (224.9)	6612 (260.3)	6207 (244.4)	163 (358.6)	14 嵌入钢圈 EMBEDDED RING	2	SUS316L
7	6728 (264.9)	7628 (300.3)	7223 (284.4)	182 (400.4)	12/13 钢带 STRAP+螺丝 screwhead (螺栓尺寸: M8*90)	2-3	A-666, 304+A216
					11 鞍座 SADDLE (3芯以上均为3个)	2-3	TPU (S60D)
					10 密封板 SEALBOARD	2	ABS
					09 适配器 ADAPTOR	2	ABS
					08 适配器大/小型 ADAPTOR LARGE/SMALL O GLUE	4+4	三元乙丙 EPDM
					07 密封板 O型圈 SEALING PLATE O-RING	2	丁腈 NBR
					06 承载板 BEARING PLATE	2	SB-209, 6061-T651
					05 止推环 THRUST CONE	1	工程塑料 Engineering Plastic
					04 侧口螺母 SIDE DORT NUTS	2-4	SUS304
					03 侧口 SIDE PORT	2-4	超级双相钢 Super duplex SS2507
					02 侧口密封圈 SIDE PORT SEAL RING	4	EPDM 512
					01 壳体 SHELL	1	FIBER GLASS +EPOXY

SIGNATURE			河北成达水处理科技有限公司 Hebei Chengda Water Technology Co., Ltd	
	NAME	DATE		
设计	卢景伟	2022.12.27		
审核				
审批			型号 TYPE	单位 UNIT:
			W80S1000-3"	MM
THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY			仅供参考, 零部件以图纸为准, 变更不另行通知	